

## **NOTICE TO MARINERS**

## **Berth Depths**

All depths are given meters above chart datum. The design depth is the maximum permissible depth according to the quay wall structure. Survey depth is the minimum depth found as a result of survey. Approach Depth is the minimum depth leading to the berth on which tidal windows are calculated. Depths in red are shallower than previous issues of this Notice to Mariners.

Area	Survey Depth (m)				
Outer Fairway to VTS	9.4				
VTS to corner berth OB1	9.5				
OB1 west to North Wall Quay Light	7.8				
Alexandra Basin East	7.7				
Alexandra Basin West	North of RoRo Berth <b>7.5</b> South of RoRo Berth <b>6.8</b>				
North Wall Quay Light to Buoy 20	7.5				
Buoy 20 to East Link Bridge	6.5				
River west of East Link Bridge	3.8				
Dun Laoghaire Harbour	5.1				

The Master remains responsible for maintaining a safe Under Keel Clearance (UKC) at all times.

Minimum UKC for a manoeuvring vessel in the channel, fairway or basins is 1.0m

Minimum UKC for a vessel alongside a berth is 0.5m over all stages of the tide.

The latest sounding charts are published on www.dublinport.ie/information-centre/soundings/

Berth	Length (m)	Bollards	Berth Pocket (m)	Berth Design (-m)	Berth Survey (-m)	Approach Depth	Berth	Length (m)	Bollards	Berth Pocket (m)	Berth Design (-m)	Berth Survey (-m)	Approach Depth
SRJQ 6&7				6.5	4.5	3.5	0B1	185		30 35	10.4	10.3 10.0	7.7
SRJQ8				6.5	5.0	3.8	0B2	185		30 35	10.7	10.5 10.4	7.4
SRJQ9				6.5	4.8	3.8	0B3	185		30	10.1	10.0	7.4
SRJQ 10				6.5	4.0	3.8	0B4	160		25	6.5	6.1	6.1
NWQ 17		Pontoons		6.5	2.5	2.5	41	150	1-9 9-10.5	24	7.4	7.1	7.1
18	200		25	6.5	6.5	6.5	42	110	10.5-17	30	11.0	10.9	7.8
19	180		25	6.5	6.5	6.5	43	130	17-25	30	11.0	10.7	7.8
20			25	6.5	6.5	6.5	44	80	25-29.5	30	11.0	10.7	7.8
21/22	200		25	6.5	6.5	6.5		old ramp	29.5 - 36.5		8.0	6.8	
26	220	1-16			6.8	6.8	45	160	37-48	25	8.7	8.5	8.5
27	220	1-16			6.8	6.8	46	360	0-12	30	11.0	10.7	9.3
CBQ	70	1-6	-	-	5.8	5.8	47		12-23	30	11.0	10.8	9.3
28	120	1-9	30	7.9	7.9	7.5	48			30	11.0	10.9	8.0
29	100	10-18	35	10.3	8.9	7.5	49	210		34	11.0	9.1	9.1
30	180	7-19	35	10.3	8.8	7.5	49a	80		27	8.0	7.8	7.8
31	105	19-23	35	9.8	8.8	7.5	50a	170		30	11.0	10.6	7.7
32	370	Ramp-9	50	9.5	8.9	7.5	50N	370	2-11	35	9.5	9.2	7.6
33		9-26	50	9.5	8.8	7.5	50S		11-23	35	9.5	9.3	7.6
34		26-30	50	9.5	8.1	7.5	51	200		35	8.0	7.8	7.6
35	100	30-37	25	9.5	9.3	7.8	51a	180		Basin	8.0	7.7	7.7
36	200	Corner-8	30	10.3	10.3	7.7	52	200		30	8.0	7.9	7.7
37 38	300	8-1 2-8	30 30	10.3 10.3	10.3 10.2	7.7	53	175		30	6.0	6.0	6.0
39	300	2-8 8-14	30	10.3	10.2	7.7 7.7	Pilot Stn					1.5	
40		14-20	30	10.3	10.3	7.7	Port Ops					6.5	
40		14-20	30	10.5	10.5	1.1	Fort ups					0.5	

Captain Michael McKenna | Harbour Master | 07 February 2025

